

AMENDMENTS TO THE CLAIMS

This listing will replace all prior versions, and listings, of claims in the application:

**Listing of Claims**

1. (Cancelled)
2. (Cancelled)
3. (New) Stackable box for perishable goods, comprising:  
a bottom, two longer sides, and two front sides configured to define four corners,  
each of the front sides having two end extensions with transverse folding lines so that  
the end extensions once folded and assembled form four prismatic reinforcements, one in each  
of the four corners,

wherein the end extensions have four transverse folding lines each, which define,  
together with and starting from an initial folding line which separates the front side from its  
corresponding end extension, first, second, third, fourth and fifth sectors, the first sector being  
defined between the initial folding line and an innermost of the four transverse folding lines in  
the end extension, the second sector being defined between the innermost and the consecutive  
outer of the four transverse folding lines,

such that once the stackable box is assembled:

each first sector is adjacent to an inner face of a longer side;  
each second sector is arranged in a diagonal disposition with respect to a corner;  
each third sector is adjacent to an inner face of a front side;  
each fourth sector is arranged in a diagonal disposition opposite a dihedron  
formed by a first sector and a correlative front side, and is oriented at right angles to a second  
sector; and

each fifth sector is attached to an inner face a half of the diagonal sector; and  
wherein the second sector, and the fourth and fifth sectors respectively have first and  
second flanges, respectively, at their upper edge, the second flange extending from half of the  
fourth sector to half of the fifth sector; this second flange, in the assembled box, comprising two  
semi-flanges, one semi-flange perpendicular to the first flange and the other semi-flange

adjacent to a half of the first flange, the first and second flanges thereby forming a reinforcement;

and wherein the second sector, and the fourth and fifth sectors respectively have first and second notches, respectively, at their bottom edges, defined in an opposing and complementary way with respect to the corresponding first and second flanges, and adapted such that when stacking two or more stackable boxes, the first and second flanges are positioned in recesses corresponding to the first and second notches.

4. (New) Stackable box for perishable goods, as defined in claim 3, wherein the front sides are provided with a horizontal upper bridge each, which horizontal upper bridge is provided in its outermost portions with holes for accommodating the first and second flanges.